



## Dry PTFE Lube, 10 Wt Oz

No. 03044 | Item# 1003302 | Case# 1003301

### Product Description

Contains PTFE, the advanced Dry Film lubricant technology from DuPont®. Penetrates and bonds to most surfaces. Prevents sticking, reducing friction and wear and is highly resistant to oil, dust and dirt build-up. NSF H2 Registered.

### Applications

Hinges, locks, catches, pulleys, conveyors, machine parts, chutes & slides, coin mechanisms, window guides, drawers, rollers, control buttons, switches, electrical wires & harnesses.

### Unit Package Description

16 Ounce Aerosol

### Brand

CRC

### Generic Description 1

Dry Film Lubricant

### Net Fill

10 Wt Oz

### UPC Code

078254030449

### Unit Dimensions

7.75H x 2.63W x 2.63D in

### Units Per Case

12

### Case Dimensions

8.1H x 8.3W x 11.1D in

### Cases Per Pallet

133

### Case Weight

11 lbs

### I 2 of 5 Code

30078254030440

### Appearance

Hazy White Suspension in Liquid

### Base Type

PTFE

### Flash point (F)

<20°F

### Flash point (C)

<-7°C

### Flammability Class - CPSC

Flammable

### Spec Gravity Concentrate

0.73

### Plastic Safe

Yes

### Film Type

Micro-Thin and Dry

### Film Thickness

0.05 to 0.1 Mil

### Evaporation Rate

Fast

Last revised: 9/5/2019

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)



Working Temp (F)	-40 to 450°F
Working Temp (C)	-40 to 232.2°C
Propellant	Hydrocarbon
NSF Category Code	H2
NSF Number	121621
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	98
VOC g/L (Consumer Product def)	715.4
VOC lbs/gal (Consumer Prod def)	5.96
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with IPA or hexane if wet; hard rubbing when dry.